



ZPMV2.E252691 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's IQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

KUNSHAN UNISTAR ELECTRONICS CO LTD
900 HANPU RD
KUNSHAN, JIANGSU 215341 CHINA

E252691

Type	Cond Width		Cond	SS/ DSO	Max	Solder		Max	Flame	Meets	C
	Min	Edge			Area	Limits	Oper	UL796			
	mm(in)	mm(in)	Thk	Diam	C	sec	C	Class	DSR	I	
Multilayer metal base printed wiring board, employing metal base laminate.											
2CVO	0.24 (0.009)	0.24 (0.009)	34 (1.34) Int:102	SS	89 (3.5)	300	60	110	V-0	-	-
ASDL-EMC	0.10 (0.004)	0.30 (0.012)	17 (0.67) Int:34	SS	50.8 (2.0)	288	10	90	V-0	All	-
ASDL-IT	0.10 (0.004)	0.30 (0.012)	35 (1.38) Int:35	SS	88.9 (3.5)	280	10	50	V-0	-	-
Multilayer printed wiring boards.											
008VO	0.05 (0.002)	0.13 (0.005)	17 (0.67) Int:34	DS	76.2 (3.0)	280	10	130	V-0	All	-
PWB-M	0.08 (0.003)	0.24 (0.009)	17 (0.67) Int:34	DS	25.4 (1.0)	265	10	105	V-0	All	-
PWB-M1	0.10 (0.004)	0.30 (0.012)	17 (0.67) Int:34	DS	25.4 (1.0)	265	10	130	V-0	All	-
Single layer metal base printed wiring board, employing metal base laminate.											
1PVO	0.20 (0.008)	0.20 (0.008)	34 (1.34)	SS	89 (3.5)	300	60	110	V-0	-	-
A5VO	0.10 (0.004)	0.30 (0.012)	17 (0.67)	SS	50.8 (2.0)	300	60	90	V-0	-	-
AS-EMC	0.10 (0.004)	0.30 (0.012)	34 (1.34)	SS	50.8 (2.0)	288	10	90	V-0	-	-
AS-IT	0.10 (0.004)	0.30 (0.012)	35 (1.38)	SS	88.9 (3.5)	280	10	50	V-0	All	-
AS-NY	0.10 (0.004)	0.30 (0.012)	35 (1.38)	SS	88.9 (3.5)	280	10	50	V-0	-	-
ASL-HS	0.10 (0.004)	0.30 (0.012)	35 (1.38)	SS	88.9 (3.5)	280	10	90	V-0	All	-
Single layer metal base printed wiring board, employing metal base laminate, flammability only Recognition.											
ITVO	-	-	-	SS	-	300	60	-	V-0	-	-
Single layer printed wiring boards.											
003VO	0.05 (0.002)	0.13 (0.005)	17 (0.67)	DS	76.2 (3.0)	280	10	130	V-0	All	-
PWB-D	0.08 (0.003)	0.24 (0.009)	17 (0.67)	DS	25.4 (1.0)	265	10	105	V-0	All	-
PWB-D1	0.10 (0.004)	0.30 (0.012)	17 (0.67)	DS	25.4 (1.0)	265	10	130	V-0	All	-



Marking: Company name or trademark or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2011-10-27

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

©2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".